

QMFZ2.E249605 - Plastics - Component

Plastics - Component

SUZHOU OMA Y OPTICAL MATERIALS CO LTD
 158-30 HUASHAN RD
 SND
 SUZHOU, JIANGSU 215011 China

E249605

Dsg	Color	Min Thk mm	Flame Class	H W I	H A I	Elec Str	RTI Mech Imp	H V T	D 4 9 5	C T I	
											R
Polycarbonate (PC) furnished as film or sheet											
V11, V42, V32, V41, V21, V31, V61, V71, V11-P, V42-P, V31-P, V32-P, V41-P, V21-P, V61-P, V71-P											
	NC	0.20-0.22	VTM-0	-	-	80	80	80	-	-	-
V11B , V42B, V32B, V41B,V21B, V31B, V61B, V71B, V11B-P, V42B-P, V31B-P, V32B-P, V41B-P, V21B-P, V61B-P, V71B-P											
	BK	0.1	VTM-2	-	-	80	80	80	-	-	-
		0.25	VTM-0	-	-	80	80	80	-	-	-
Polycarbonate (PC) furnished as sheets											
G11,G11W, G11B, SB11, SG11, FG11, G11-R, G11-BU, G11W, FG(a), LSC(a), EHF(a),OMR(a)-UV, C71-A, C71-B, C71-C, ST(a), OM(a)-UV,G(a)W,G11B, IMD11, LCD11, LCD41, LCD61, LCD11B, T11, UV11, SR11, LC11, LC21, LC32, LC42, LC21B, LC11B, LC32B, LC21W, LC32W, LC42B, LC42W											
	NC	0.121	V-2	-	-	80	80	80	-	-	-
		1.0-1.1	V-2	-	-	80	80	80	-	-	-
G42, G51, G42F, G21F, G32, G32F, G52, G21, G41, G41F, G21B, G42B, G61, G71, IMD42, IMD41, LD21, LD21W, LD32, LD42, LD42W, LD52W, LD41W, LD21W-F, LD42W-F, T41, T32F, SR42, SR41, SR21											
	NC	0.120-0.132	VTM-2	-	-	80	80	80	-	-	-
		0.5-0.55	V-2	-	-	80	80	80	-	-	-
	OM(a), BLC(a)(b), GAP(a)	0.075	VTM-2	-	-	80	80	80	-	-	-
		0.125	VTM-2	-	-	80	80	80	-	-	-
		0.5	V-2	-	-	80	80	80	-	-	-
		0.8	V-2	-	-	80	80	80	-	-	-
		3.0	V-2	-	-	80	80	80	-	-	-
	OMF(a), BLC(a)(b)F, RHA(a)	0.8	V-0	-	-	80	80	80	-	-	-

		3.0	V-0	-	-	80	80	80	-	-	-
U(a), U(a)-P	NC	0.110-0.250	VTM-0	-	-	80	80	80	-	-	-
		0.370-0.8	V-0	-	-	80	80	80	-	-	-
U(a)B, U(a)B-P	BK	0.110-0.250	VTM-0	-	-	80	80	80	-	-	-
		0.370-0.8	V-0	-	-	80	80	80	-	-	-
Polycarbonate (PC) furnished as sheets or rolls											
G11-N	NC	0.175-0.19	V-2	-	-	80	80	80	-	-	-
SE11, SE21, SE41, SE42, SE31, SE61, SE71, SE32, SE52, SE51, SE62, SE72											
	NC	0.125	V-0	0	4	80	80	80	-	-	-
		0.25	V-0	0	4	80	80	80	-	-	-
		0.8-0.88	V-0	0	0	80	80	80	-	-	-
SE42B, SE21B, SE41B, SE42W, SE42B-F, SE41B-F, SE32B, SE31B, SE61B, SE71B, SE52B, SE51B, SE62B, SE72B, SE21W, SE41W, SE32W											
	BK	0.25	V-0	0	0	80	80	80	-	-	-
		0.8-0.88	V-0	0	0	80	80	80	-	-	-
Polycarbonate (PC)/Polymethyl Methacrylate (PMMA) furnished as film or sheets											
GMC	NC	0.5	HB	-	-	50	50	50	-	-	-
		2.0	HB	-	-	50	50	50	-	-	-
Polycarbonate/Polybutylene Terephthalate (PC/PBT) furnished as sheets or rolls											
SE900	NC	0.125-0.14	VTM-0	4	4	75	75	75	-	-	-
		0.50-0.55	V-0	4	0	75	75	75	-	-	-
Polypropylene (PP) furnished as pellets											
ESC(a)B, ESC-HF(a)B, BSC(a)B, ESC(a)B-ECO, ESC(a)B-(b)											
	BK	0.3-0.75	V-0	-	-	65	65	65	-	-	1
ESC(a)W, ESC-HF(a)W, BSC(a)W, ESC(a)W-ECO, ESC(a)W-(b)											
	WT	0.3-0.75	V-0	-	-	65	65	65	-	-	1
SC(a)B	BK	0.38 - 0.74	V-0	4	0	65	65	65	-	-	0
		0.75 - 0.9	V-0	4	0	65	65	65	-	-	-

(a) - May be followed by a two digit suffix [00-99] inclusive, indicating textures of both sides of the film/sheet

(b) - May be 001-999 representing different client designations.

Marking: Company name, material designation On container, wrapper Or finished part.

Last Updated on 2022-02-09



并不是所有出现在本数据库中的公司名称和产品都满足了UL跟踪检验服务的要求。只有带有UL标志的产品，才应该被视为经过UL认证，并满足UL跟踪检验服务的要求。注意查看产品上的标志。

UL允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经UL允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“©2023 UL LLC.”